


TINKER & RASOR



CORROSION MITIGATION INSTRUMENTATION

PRODUCT DATA SHEET

MODEL TriStar 50 Amp GPS Interrupter

Features:

- Interrupt up to 50 Amp @ 120 Volt (6,000 watt Max.)
- GPS Timing for Synchronization with other units
- Cycle between 000.005s and 999.999s
- 115v - 230v Auto sensing AC power supply
- Removable magnetic mount GPS Antenna
- Manual Sync feature
- 10 Program memory
- Transfer program information to multiple units
- Internal cable storage
- Secure with lid open or closed
- All connections made from outside of case
- Keypad operation with large LCD screen

Construction:

- Rugged carrying case design for rough field use.
- Sealed against dust and water (not immersion)
- Solid state circuitry, no mercury relays
- Reinforced locking rings, lock with lid open or closed
- Internal storage of cables

Applications:

- CIPS
- DCVG
- CP Monitoring
- Pipe - to - Soil Potentials
- Interrupt Ground beds

Specifications:

50 Amp max, AC or DC
120 Volt max, AC or DC
Display: 0°C to 50°C (32°F to 122°F)
Powered from 115v or 230v (60/50 cycle) AC

Dimensions:

10.62" x 9.68" x 6.87", 15 lbs
(269.79mm x 245.87mm x 174.50mm, 6 kg)

Shipping Dimensions:

11" x 7.5" x 10.5", 16 lbs
(279.40mm x 190.50mm x 266.70mm, 7 kg)



MODEL TriStar GPS Current Interrupter

DELIVERY: **Immediately from STOCK**
F.O.B. San Bernardino, CA USA
SERVICE: **24-hour Turn-Around**
TERMS: Net30 Days, on approval of credit
WARRANTY: **90 Days**, parts and labor

AVAILABLE FROM STOCK