









# Solid-State Reference Electrodes

Stelth® Model Name	Model: Chemistry	Use	Minimum Service Life	Size	Standard Lead Wire
<b>Stelth® 7: 1 cm<sup>2</sup> New Design</b> 	SRE-022-ND: Cu-CuSO <sub>4</sub> SRE-025-ND: Ag-AgCl SRE-028-ND: Zn-ZnSO <sub>4</sub> SRE-046-ND: Pd-PdCl <sub>2</sub>	<b>IR-Free Probe</b> <b>1 cm<sup>2</sup> Coupon</b> On-Off Potential Depolarization Potential DC Current Density	30 years	2" (63.5 mm) width x 11" (280 mm) length.	Any length of RHH-RHW black #16-3 tray cable wire available.
<b>Stelth® 7: 10 cm<sup>2</sup> New Design</b> 	SRE-023-ND: Cu-CuSO <sub>4</sub> SRE-026-ND: Ag-AgCl SRE-029-ND: Zn-ZnSO <sub>4</sub> SRE-047-ND: Pd-PdCl <sub>2</sub>	<b>IR-Free Probe</b> <b>10 cm<sup>2</sup> Coupon</b> On-Off Potential Depolarization Potential DC Current Density	30 years	2" (51 mm) width x 15" (381 mm) length.	Any length of RHH-RHW black #16-3 tray cable wire available.
<b>Stelth® 7: Rocket</b> 	SRE-031: Cu-CuSO <sub>4</sub> SRE-032: Ag-AgCl SRE-033: Zn-ZnSO <sub>4</sub> SRE-049: Pd-PdCl <sub>2</sub>	<b>IR-Free Probe</b> <b>100 cm<sup>2</sup> Coupon</b> On-Off Potential Depolarization Potential DC Current Density	30 years	2" (51 mm) width x 12.75" (324 mm) length.	Any length of RHH-RHW black #16-5 tray cable wire available.
<b>Stelth® 7: AC-20 cm<sup>2</sup></b> 	SRE-024-AC20: Cu-CuSO <sub>4</sub> SRE-027-AC20: Ag-AgCl SRE-030-AC20: Zn-ZnSO <sub>4</sub> SRE-048-AC20: Pd-PdCl <sub>2</sub>	<b>AC Mitigation Monitoring</b> Depolarization Potential On-Off Potential DC & AC Current Density Native Potential	30 years	2" (51 mm) width x 16" (406.5 mm) length.	Any length of RHH-RHW black #16-5 tray cable wire available.
<b>Stelth® 7: AC-200 cm<sup>2</sup></b> 	SRE-031-AC200: Cu-CuSO <sub>4</sub> SRE-032-AC200: Ag-AgCl SRE-033-AC200: Zn-ZnSO <sub>4</sub> SRE-049-AC200: Pd-PdCl <sub>2</sub>	<b>AC Mitigation Monitoring</b> Depolarization Potential On-Off Potential DC & AC Current Density Native Potential	30 years	2" (51 mm) width x 21.25" (540 mm) length.	Any length of RHH-RHW black #16-5 tray cable wire available.
<b>Stelth® 7: Triton Rocket</b> 	SRE-031-BE-V: Cu-CuSO <sub>4</sub>	<b>AC Mitigation Monitoring</b> Depolarization Potential On-Off Potential DC & AC Current Density Native Potential	30 years	2" (51 mm) width x 21.25" (540 mm) length.	Any length of RHH-RHW black #16-5 tray cable wire available.

*Built to the standards of American Innovations.  
Contact 1 (800) 229-3404 for pricing and availability.*

Distributed by:



**TECNOLOGÍA TOTAL**  
[www.tecnologiatotal.net](http://www.tecnologiatotal.net)

**1 to 3 day delivery.**

**Infinite shelf life, infinite stability, and 30-year design life.**

**Stelth® reference electrodes are available in four chemistries:**

**Copper-Copper Sulfate** (Cu-CuSO<sub>4</sub> – for areas with chloride plus bromide levels up to 1,000 parts per million) color-coded yellow

**Silver-Silver Chloride** (Ag-AgCl – for areas with chloride plus bromide levels near 19,000 parts per million (seawater) color-coded blue

**Zinc-Zinc Sulfate** (Zn-ZnSO<sub>4</sub> – for areas with chloride plus bromide levels up to 1,000 parts per million) color-coded red

**Palladium-Palladium Chloride** (Pd-PdCl<sub>2</sub> – Hydrocarbon-proof HCP™ that are immune to hydrocarbons and chloride count issues, and therefore ideal for chloride and hydrocarbon level problem zones) color-coded orange

**Material:** High-impact ABS, ceramic plug with Moisture Retention Membrane (MRM™).

**Each cell is Individually tested** for internal resistance, continuity, IR-drop, sensitivity, and stability. Stelth® reference electrodes are then **certified**, with a **unique serial number**, allowing for **traceability of any cell throughout its lifetime.**

Our proprietary **Moisture Retention Membrane MRM™** traps moisture and the internal chemistry inside the reference electrode; the MRM™ also **prevents contaminated ground water** from entering the reference electrode.

**Stelth® reference electrodes can be frozen;** they come back to life once thawed.

A major breakthrough – the **hydrocarbon-proof (HCP™) Stelth®** reference electrode that **can be used in all environments.** If you have facilities contaminated by gasoline, crude oil, brake fluid, transmission fluid, et cetera and are unable to get a potential reading, the HCP™ stationary or portable Stelth® reference electrode will solve your problem.

**Working Temperature Range:** 32°F to +176°F (0°C to 80°C).

**Material Temperature Range:** -60°F to +185°F (-51°C to 85°C).

© **BORIN Manufacturing** | 5741 Buckingham Parkway, Unit B, Culver City, CA 90230, USA | 310-822-1000 | Fax: 310-338-3434 | [www.borin.com](http://www.borin.com) | 2016-11-08

Distributed by:



**TECNOLOGÍA TOTAL**  
[www.tecnologiatotal.net](http://www.tecnologiatotal.net)