



# MODEL RF-IT

## *Above Ground Insulator Tester*

### **FEATURES:**

- *Hand Held Instrument*
- *Easily locates shorted bolts, replaces bolt to bolt*
- *Use on structure with or without CP*
- *Uses Radio Frequency to test effectiveness of above ground insulators*
- *Auto Shut-Off feature*



***Test Above Ground Pipeline Insulators to Pinpoint the Precise Contact Point.***



*Distributed by:*



**TECNOLOGÍA TOTAL**  
[www.tecnologiatotal.net](http://www.tecnologiatotal.net)

[teststations.com](http://teststations.com)

[detectron.com](http://detectron.com)

***Info@tinker-rasor.com | tinker-rasor.com***

Tinker & Rasor quality is found in our products, our people and our customer service.



TECNOLOGÍA TOTAL  
www.tecnologiaatotal.net

# TINKER & RASOR

## PRODUCT DATA SHEET | EXPLORING ELECTRODES

### RF-IT FEATURES:

- Move bolt to bolt to find contact
- Use on structures with or without CP
- Uses Radio Frequency to test effectiveness of above ground insulators
- Auto Shut-Off feature

### INCLUDES

- Probe, Red with lead wire and needle point tip
- Probe, Black with needle point tip
- Additional needle tips, stored in small black vinyl tubes
- 9 volt battery
- Instructions Manual
- Warranty Card

### CONSTRUCTION:

Housed in tough polypropylene case with handle.

RF-IT comes with (2) sets of needle points

### APPLICATIONS:

- Above Ground Insulators
- Pinpoints The Precise Contact Point
- Use Regardless of CP or Other Current / Voltage Present on Structure

### SPECIFICATIONS:

Battery Operated  
9 volt battery (replaceable)  
Cables and Probes included

### DIMENSIONS:

8" length x 4" width x 3" depth  
Operating Weight: 2 lbs.  
Shipping Weight: 3 lbs.

**DELIVERY:** Immediately from STOCK  
F.O.B. New Braunfels, TX USA

**SERVICE:** 24-hour Turn-Around

**TERMS:** Net 30 Days, on approval of credit

**WARRANTY:** 90 Days, parts and labor

### MODEL RF-IT

### Above Ground Insulation Tester

Test above ground pipeline insulators to pinpoint the precise contact point.



The RF-IT emits an audible beep. When the operator gets closer to the point of contact the unit starts beeping faster. At the same time, the LCD meter moves from left to right.



**AVAILABLE FROM STOCK**

**tinker-rasor.com**